



PREMIERTRAK 450

The Powerscreen® Premiertrak 450 is high-performance primary jaw crushing plant, designed for operators in quarrying, demolition, recycling, and mining applications. The Premiertrak 450 boasts a two-piece grizzly feeder allowing better material flow towards the chamber. User benefits include quick set up time and direct drive chamber for efficient fuel consumption. Additional options include single deck post screen, pre-screen and bypass conveyor.



✓ APPLICATIONS

AGGREGATE



Sand & gravel
Blasted rock
River rock

RECYCLING



C&D waste
Overburden
Foundry waste

MINING



Processed ores
Processed minerals

TECHNICAL HIGHLIGHTS ✓



INCREASED PRODUCTIVITY

- Superior tunnelling reduces the risk of rebar snagging giving excellent machine uptime.
- Class leading output due to new, larger bearing jaw chamber
- Jaw level sensor option promotes material flow by optimising feeder speeds, increasing daily productivity.
- Powerscreen Pulse intelligent monitoring as standard.



VERSATILITY

- Ideal for C&D waste / recycling applications with hydraulic deflector plate and hydraulically raise / lower product conveyor options.
- Jaw unblock option allows for rapid, safe and controlled clearance of the chamber.



SERVICEABILITY

- Centralised low level hydraulics and electrics.
- Unrestricted access to both sides of the power unit.





TECHNICAL SPECIFICATION



1 HOPPER

Hydraulic folding hopper
Length: 4.75m (15' 7")
Width: 2.5m (8' 2")
Capacity: 10m³ (13 cu. yd.)

2 CRUSHER

High capacity single toggle jaw
Chamber size: 1100mm x 700mm
(44" x 28")
Min CSS: 50mm (2")
Max CSS: 150mm (6")

3 PRODUCT CONVEYOR

Width: 1000mm (40")
Discharge height: 3.9m (12' 10")

4 FEEDER

Vibrating grizzly feeder
Length: 4.25m (13' 11")
Width: 1.10m (3' 7")

5 TRACKS

Width: 500 mm (1' 8")


6 POWER UNIT

Tier 3 Equivalent: CAT C9.3 6 230kW
(308hp)
Tier 4F / Stage V: Scania DC9 202kW
(275hp)
Fuel tank capacity: 500 L (120 US G)



DIMENSIONS

WORKING



TRANSPORT

Length: 16.1m (52' 10")
Width: 3.4m (11' 2")
Height: 2.8m (9' 2")

WEIGHT*

Tier 3: 49,125kg (108,302lbs)
Tier 4F: 49,162kg (108,383lbs)
Stage V: 49,165kg (108,390lbs)

*Weights may vary depending on options

GET IN TOUCH

Dungannon

200 Coalisland Road, Dungannon,
Co Tyrone, BT71 4DR, Northern Ireland
Tel: +44 (0) 28 87 718 500
Fax: +44 (0) 28 87 747 231

Louisville

11001 Electron Drive,
Louisville, Kentucky, 40299 USA
Tel: +1 502 736 5200
Fax: +1 502 736 5202



www.powerscreen.com

The material in this document is for information only and is subject to change without notice. Powerscreen assumes no liability resulting from errors or omissions in this document, or from the use of the information contained herein. Due to continual product development we reserve the right to change specifications without notice. Product performance figures given in this brochure are for guidance purposes only, this information does not constitute an expressed or implied warranty or guarantee, but shows test examples provided by Dealers. These results will vary depending on crusher chamber settings, screen media and sizes, feed source and types of material being processed. Photographs are for illustrative purposes only, some or all of the machines in the illustrations may be fitted with optional extras. Please check with your Dealer for details on optional extras. All machines are CE Approved.

Powerscreen® is a registered trademark of Terex GB Limited in the United States of America and many other countries. Copyright 2023 Terex GB Limited. Published and Printed in November 2023.